# Spring-loaded test probe

# GKS-181 354 080 A 0803

Item GKS-181-0018

GO TO PRODUCT

ingun®
Partner for Future Technology







## General data

| | |
|---|---|
| Product group: | ICT / FCT (in-circuit test and function test |
| Sub-product group: | Fine-pitch |
| Series: | GKS-181..0x installation without KS |
| Grid: | 1.27 mm [50 mil] |
| Contacting from: | Pad, pin, posts |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | No |
| Type of test probe connection: | Plug |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible connector(s): | SE-111 |
| Min. temperature: | - 40 °C [- 104 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6c |

## Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 2 A |
| Typical resistance (Ri): | <20 mOhm |

## Mechanical data

| | |
|---|---|
| Total length: | 39.8 mm [1.56 in] |
| Barrel diameter: | 1 mm [.039 in] |
| Maximum stroke: | 7.5 mm [.295 in] |
| Spring pre-load: | 0.22 N [.791 ozf] |
| Collar height: | 03 |
| Spring force at working stroke: | 0.8 N [2.87 ozf] |
| Recommended working stroke: | 5.5 mm [.216 in] |

## Tip style data

| | |
|---|---|
| Tip style: | 54 4-point crown, special length |
| Tip diameter: | 0.8 mm [.031 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |

# Spring-loaded test probe
# **GKS-181 354 080 A 0803**

Item GKS-181-0018

GO TO PRODUCT

ingun®
Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB