# Spring-loaded test probe


# GKS-113 306 400 A 0610


Item GKS-113-0896

GO TO PRODUCT

ingun®
Partner for Future Technology

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available




## General data

| | |
|---|---|
| Product group: | ICT / FCT (in-circuit test and function test |
| Sub-product group: | Metric standard |
| Series: | GKS-113 |
| Grid: | 4.5 mm [177 mil] |
| Contacting from: | Pin, Post, Flat contact |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible receptacle(s): | KS-113, KS-113 23 |
| Min. temperature: | - 40 °C [- 104 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6c |

## Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 5 A |
| Typical resistance (Ri): | <30 mOhm |

## Mechanical data

| | |
|---|---|
| Total length: | 35.3 mm [1.38 in] |
| Barrel diameter: | 2.65 mm [.104 in] |
| Maximum stroke: | 5.3 mm [.208 in] |
| Spring pre-load: | 0.21 N [.755 ozf] |
| Collar height: | 10 |
| Spring force at working stroke: | 0.6 N [2.15 ozf] |
| Recommended working stroke: | 4 mm [.157 in] |

## Tip style data

| | |
|---|---|
| Tip style: | 06 serrated |
| Tip diameter: | 4 mm [.157 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |


# Spring-loaded test probe

## GKS-113 306 400 A 0610

Item GKS-113-0896

GO TO PRODUCT

ingun®
Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB