
Spring-loaded test probe

GKS-038 302 028 A 0400 V

Item GKS-038-0002

GO TO PRODUCT

ingun®
Partner for Future Technology



General data

Product group:	ICT / FCT (in-circuit test and function test
Sub-product group:	Fine-pitch
Series:	GKS-038 V pre-wired
Grid:	0.64 mm [25.1 mil]
Contacting from:	Pin, posts, bead, flat contact
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	No
Type of test probe connection:	vorkonfektioniert
Adjustable installation height:	No
Non-rotating:	No
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	1 A
Typical resistance (Ri):	<100 mOhm

Mechanical data

Total length:	24 mm [.944 in]
Barrel diameter:	0.38 mm [.014 in]
Maximum stroke:	2.5 mm [.098 in]
Spring pre-load:	0.14 N [.503 ozf]
Collar height:	00
Spring force at working stroke:	0.4 N [1.43 ozf]
Recommended working stroke:	2 mm [.078 in]

Tip style data

Tip style:	02 flat
Tip diameter:	0.28 mm [.011 in]
Tip style surface:	A gold
Tip style material:	3 CuBe


Spring-loaded test probe

GKS-038 302 028 A 0400 V

Item GKS-038-0002

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB