Dipole / coaxial probe


DPS-465 302 050 A 4002 M


Item DPS-465-0002

GO TO PRODUCT

ingun®
Partner for Future Technology







Dipole / coaxial probe

DPS-465 302 050 A 4002 M

Item DPS-465-0002

GO TO PRODUCT

ingun®
Partner for Future Technology

General data

Product group:	DPS dipole test probe
Series:	DPS-465
Sub-series:	DPS-465 M, screw-in
Grid:	3.5 mm [137 mil]
Installation type:	Screw-in
Floating mount:	No
Non-rotating:	No
Continuous plunger:	No
Interface of compatible assembly:	SE-215 plug, press-in, for DPS-465, SKS-465 (MF, SF)
Compatible assembly interface gender :	F signal conductor female / socket
KS sub-series:	KS-465 M, KS-465 M-F, screw-in version
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Outer conductor data

Outer conductor tip style:	02 flat
Outer conductor tip style diameter:	2.26 mm [.088 in]
Spring force of entire outer conductor at working stroke:	3 N [10.7 ozf]
Outer conductor working stroke:	4 mm [.157 in]
Outer conductor maximum stroke:	5 mm [.196 in]
Exchangeable outer conductor:	No
Outer conductor max. current load capacity:	10 A

Inner conductor data

Inner conductor tip style:	02 flat
Inner conductor tip style diameter:	0.5 mm [.019 in]
Inner conductor tip style material:	3 CuBe
Inner conductor tip style surface:	A gold
Number of inner conductors:	1
Exchangeable inner conductor:	No
Inner conductor working stroke:	4 mm [.157 in]
Spring force of each inner conductor at working stroke:	1 N [3.59 ozf]
Inner conductor maximum stroke:	5 mm [.196 in]
Inner conductor max. current load capacity:	2 A

Electrical data

Dielectric strength:	1 kV

Mechanical data

Total spring force at working stroke:	4 N [14.3 ozf]
Total length:	44.8 mm [1.76 in]
Barrel diameter:	2.65 mm [.104 in]
Installation height without receptacle:	10.2 mm [.401 in]
Torque in receptacle:	3 - 5 cNm [.265 - .442 lbf·in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com