# High-Current Probe


## HSS-120 302 230 A 1510


Item HSS-120-0007

GO TO PRODUCT

ingun®
Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights




### General data

| | |
|---|---|
| Product group: | High-current test probe |
| Sub-product group: | Standard HSS (press-in) |
| Series: | HSS-120 |
| Grid: | 4 mm [157 mil] |
| Contacting from: | Pin, posts, bead, flat contact |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible receptacle(s): | KS-113, KS-113 23 |
| Min. temperature: | - 100 °C [- 212 °F] |
| Max. temperature: | + 200 °C [+ 392 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 30 A |
| Typical resistance (Ri): | <10 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 35.3 mm [1.38 in] |
| Barrel diameter: | 2.65 mm [.104 in] |
| Maximum stroke: | 5.3 mm [.208 in] |
| Spring pre-load: | 0.39 N [1.40 ozf] |
| Collar height: | 10 |
| Spring force at working stroke: | 1.5 N [5.39 ozf] |
| Recommended working stroke: | 4 mm [.157 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 02 flat |
| Tip diameter: | 2.3 mm [.090 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |

HIGH-CURRENT TEST PROBE


# High-Current Probe

## HSS-120 302 230 A 1510

Item HSS-120-0007

GO TO PRODUCT

ingun®
Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB



Learn more about
**High-current test probe**

ingun.com

HIGH-CURRENT TEST PROBE