

### Highlights

24-pin, double sided connector

Up to 250.000 cycles

Safe transmission of data rates

### Mechanical Data

|                                    |              |
|------------------------------------|--------------|
| Temperature range                  | 0 °C - 60 °C |
| Relative Humidity (non-condensing) | 15 % - 95 %  |
| Test cycles                        | 250.000      |
| Mating Force                       | 12.0 N       |
| Unmating Force                     | 10.0 N       |
| RoHS compliant                     | yes          |
| Lead free                          | yes          |

### Electrical Data

|                  |                                        |
|------------------|----------------------------------------|
| PWD data         | 90.0 Ohm                               |
| Voltage          | 20.0 V AC (rms)                        |
| Current (power)  | 1.25 A - pin A1/A4/A9/A12/B1/B4/B9/B12 |
| Current (signal) | 0.25 A                                 |

### Test Application

|                         |                 |
|-------------------------|-----------------|
| Device under test (DUT) | USB-3.1C-F      |
| Gender                  | female / socket |

### Accessories

|                     |                 |
|---------------------|-----------------|
| Article Designation | FU 7115 - USB C |
|---------------------|-----------------|

# Technical Data // 7116-USB-3.1C-M-024-LO


USB 3.1-C - Long



**PTR HARTMANN**

A Phoenix Mecano Company

## Technical Drawing Accessorie



## Technical Drawing

