# Spring-loaded test probe


## GKS-112 306 180 R 3005 C


Item GKS-112-2564

GO TO PRODUCT

ingun®
Partner for Future Technology


- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available









1:1




### General data

| | |
|---|---|
| Product group: | ICT / FCT (in-circuit test and function test |
| Sub-product group: | Metric standard |
| Series: | GKS-112 |
| Grid: | 2.54 mm [100 mil] |
| Contacting from: | Pin, Post, Flat contact |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible receptacle(s): | KS-112 |
| Min. temperature: | - 100 °C [- 212 °F] |
| Max. temperature: | + 200 °C [+ 392 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 8 A |
| Typical resistance (Ri): | <100 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 35.7 mm [1.40 in] |
| Barrel diameter: | 1.66 mm [.065 in] |
| Maximum stroke: | 5.3 mm [.208 in] |
| Spring pre-load: | 0.9 N [3.23 ozf] |
| Collar height: | 05 |
| Spring force at working stroke: | 3 N [10.7 ozf] |
| Recommended working stroke: | 4 mm [.157 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 06 serrated |
| Tip diameter: | 1.8 mm [.070 in] |
| Tip style surface: | R rhodium |
| Tip style material: | 3 CuBe |


# Spring-loaded test probe

## GKS-112 306 180 R 3005 C

Item GKS-112-2564

GO TO PRODUCT

Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB