Receptacle

KS-550 30 E08

Item KS-55030E08


GO TO PRODUCT

Partner for Future Technology

INGUN SELECTION



1:1



General data

Product group:	Receptacles (KS)
Series:	KS-550
Sub-series:	KS-550 press-in version
Type of receptacle connection:	Solder
Press ring:	Yes
Surface area:	Gold
Collar diameter:	1.05 mm [.041 in]
Collar height:	7.6 mm [.299 in]
Knurl:	No
Vacuum-tight:	No
RoHS-compliant:	RoHS-3

Mounting hole

Mounting hole in CEM1:	0.96 - 0.98 mm [.037 - .038 in]
Mounting hole in FR4:	0.97 - 0.99 mm [.038 - .038 in]
Mounting hole with press ring in CEM1:	0.96 - 0.98 mm [.037 - .038 in]
Mounting hole with press ring in FR4:	0.97 - 0.99 mm [.038 - .038 in]

Mechanical data

Total length:	31.6 mm [1.24 in]
Outer diameter:	0.95 mm [.037 in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB