Spring-loaded test probe


GKS-416 002 300 A 5002

Item GKS-416-0001


GO TO PRODUCT

ingun®
Partner for Future Technology

INGUN SELECTION



1:1



General data

Product group:	Accessories (GKS / ADA)
Sub-product group:	PCB support pins
Series:	GKS-416
Grid:	4 mm [157 mil]
Contacting from:	Presence check
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-113 23
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	0 A

Mechanical data

Total length:	55 mm [2.16 in]
Barrel diameter:	2.65 mm [.104 in]
Maximum stroke:	11.5 mm [.452 in]
Spring pre-load:	1.23 N [4.42 ozf]
Collar height:	02
Spring force at working stroke:	5 N [17.9 ozf]
Recommended working stroke:	9.2 mm [.362 in]

Tip style data

Tip style:	002 flat, contact surface insulated
Tip diameter:	3 mm [.118 in]
Tip style surface:	A gold
Tip style material:	3 CuBe


Spring-loaded test probe

GKS-416 002 300 A 5002

Item GKS-416-0001

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

Prices and delivery times on request.
Technical changes reserved. 01/25_GB

ingun.com