Radio Frequency Probes

HF66-0007

Item number 1024463

General

Design	Coaxial Probe
Type/family	HF66
Pitch (mm/mil)	9,00 / 354
Temperature [C°]	-45°C...+100°C

Electrical specifications

Continuous current (A)	0.50
Impedance (ohm)	50.00
Frequency (GHz)	6.00
Continuous current 2 (A)	0.10

Inner contact specifications

Nominal travel 2 (mm)	0.50
Maximum travel 2 (mm)	1.50
Preload 2 (cN)	95.00
Spring force 2 (cN)	120.00

Mechanical specifications

Preload (cN)	140.00
Spring force (cN)	220.00
Nominal travel (mm)	1.50
Maximum travel (mm)	1.80
Tool size (mm)	5,0
DUT	SWG

Dimensions

Total length (mm)	35.00
Projection height (mm)	21.40
Tip style diameter (mm)	2.70
Barrel diameter (mm)	3.50
Collar diameter (mm)	20.00
Press ring diameter (mm)	20.00
Inside/outside distance (mm)	0.50
Tip style diameter 2 (mm)	0.40

Family drawing

All measurements are in mm.

Materials & surfaces

Tip style	05
Tip style 2	03
Tip style material	Brass
Tip style plating	Gold
Plunger material	Brass
Plunger plating	Gold
Barrel material	Beryllium cooper
Barrel plating	Gold
Spring material	High-grade steel
Spring plating	Uncoated
Plunger material 2	Beryllium cooper
Plunger plating 2	Gold
Spring material 2	Spring steel
Spring plating 2	Gold