Receptacle


KS-075 WL

Item KS-075WL

GO TO PRODUCT


ingun®
Partner for Future Technology

INGUN SELECTION





1:1



General data

Product group:	Wireless receptacles, (KS-WL)
Series:	KS-075
Sub-series:	KS-075 WL press-in version, wireless
Type of receptacle connection:	Wireless
Press ring:	Yes
Surface area:	Gold
Collar diameter:	1.47 mm [.057 in]
Collar height:	7.6 mm [.299 in]
Knurl:	No
Vacuum-tight:	yes (< 1 ccm / min)
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Mounting hole

Mounting hole in CEM1:	1.30 - 1.32 mm [.051 - .051 in]
Mounting hole in FR4:	1.31 - 1.33 mm [.051 - .052 in]
Mounting hole with press ring in CEM1:	1.39 - 1.40 mm [.054 - .055 in]
Mounting hole with press ring in FR4:	1.39 - 1.40 mm [.054 - .055 in]

Electrical data

Current load capacity / rated current:	2 A
Typical resistance (Ri):	<20 mOhm

Mechanical data

Total length:	43.1 mm [1.69 in]
Outer diameter:	1.32 mm [.051 in]
Spring force at working stroke:	1 N [3.59 ozf]
Recommended working stroke:	2.5 mm [.098 in]

Wireless receptacle data

Tip style material (wireless):	3 CuBe
Tip style plating (wireless):	A gold
Tip style (wireless):	07 90° 3-edged chisel, self-cleaning
Tip diameter (wireless):	0.51 mm [.020 in]
Maximum stroke (wireless):	4 mm [.157 in]
Spring pre-load (wireless):	0.6 N [2.15 ozf]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

RECEPTACLES

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com