# Spring-loaded test probe

## GKS-204 209 070 G 0810

Item GKS-204-0196

GO TO PRODUCT

ingun®
Partner for Future Technology

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Version with central beading ensure low wobble for contacting small test points







### General data

| | |
|---|---|
| Product group: | ICT / FCT (in-circuit test and function test |
| Sub-product group: | Metric standard |
| Series: | GKS-204 |
| Grid: | 2.54 mm [100 mil] |
| Contacting from: | Pad, pin |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible receptacle(s): | KS-204 |
| Min. temperature: | - 40 °C [- 104 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 5 A |
| Typical resistance (Ri): | <20 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 47.9 mm [1.88 in] |
| Barrel diameter: | 1.66 mm [.065 in] |
| Maximum stroke: | 10 mm [.393 in] |
| Spring pre-load: | 0.17 N [.611 ozf] |
| Collar height: | 10 |
| Spring force at working stroke: | 0.8 N [2.87 ozf] |
| Recommended working stroke: | 8 mm [.314 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 09 flexi-needle, self-cleaning |
| Tip diameter: | 0.7 mm [.027 in] |
| Tip style surface: | G aurun |
| Tip style material: | 2 steel |

# Spring-loaded test probe
## GKS-204 209 070 G 0810
Item GKS-204-0196

GO TO PRODUCT

ingun®
Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB