

Radio Frequency Probes

HF66-0015

Item number 1029250

General

Design	Coaxial Probe
Type/family	HF66
Pitch (mm/mil)	9,00 / 354
Temperature [C°]	-45°C...+100°C

Electrical specifications

Continuous current (A)	0.50
Impedance (ohm)	50.00
Frequency (GHz)	6.00
Continuous current 2 (A)	0.10

Inner contact specifications

Nominal travel 2 (mm)	0.80
Maximum travel 2 (mm)	3.30
Preload 2 (cN)	110.00
Spring force 2 (cN)	180.00

Mechanical specifications


Preload (cN)	120.00
Spring force (cN)	240.00
Nominal travel (mm)	2.20
Maximum travel (mm)	4.00
Tool size (mm)	9,0
DUT	SWF

Dimensions

Total length (mm)	33.60
Projection height (mm)	21.75
Tip style diameter (mm)	3.80
Barrel diameter (mm)	7.00
Collar diameter (mm)	19.68
Press ring diameter (mm)	19.68
Inside/outside distance (mm)	1.10
Tip style diameter 2 (mm)	0.40

Family drawing

All measurements are in mm.



RADIO FREQUENCY PERFORMANCE

Typical insertion loss	DC up to 3 GHz	3 GHz up to 6 GHz
Maximum	0,5 dB	0,7 dB
Typical return loss	**DC up to 3 GHz**	**3 GHz up to 6 GHz**
Minimum	12 dB	10 dB

This table shows the reference values in the middle and at the end of the recommended frequency.

Materials & surfaces

Tip style	05
Tip style 2	11
Tip style material	Brass
Tip style plating	Gold
Plunger material	Brass
Plunger plating	Gold
Barrel material	Brass
Barrel plating	Gold
Spring material	Spring steel
Spring plating	Gold
Plunger material 2	Beryllium cooper
Plunger plating 2	Gold
Spring material 2	Spring steel
Spring plating 2	Gold