Spring-loaded test probe

GKS-005 206 396 A 5000

Item GKS-005-0002

GO TO PRODUCT

ingun®
Partner for Future Technology

- Robust, compact design for harsh ICT/FCT applications with limited space
- For optimum contact at the test points (e.g. pads, vias, and pins), various tip styles in different diameters and finishes, as well as various spring forces are available. spring forces.

INGUN SELECTION





General data

Product group:	ICT / FCT (in-circuit test and function test
Sub-product group:	Short/robust GKS
Series:	GKS-005
Grid:	4.75 mm [187 mil]
Contacting from:	Pin, Post, Flat contact
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-005
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6a

Electrical data

Current load capacity / rated current:	6 A
Typical resistance (Ri):	<20 mOhm

Mechanical data

Total length:	36.1 mm [1.42 in]
Barrel diameter:	3.18 mm [.125 in]
Maximum stroke:	6.35 mm [.25 in]
Spring pre-load:	2.38 N [8.56 ozf]
Collar height:	00
Spring force at working stroke:	5 N [17.9 ozf]
Recommended working stroke:	4.4 mm [.173 in]

Tip style data

Tip style:	06 serrated
Tip diameter:	3.96 mm [.155 in]
Tip style surface:	A gold
Tip style material:	2 steel

ICT/FCT TEST PROBES

Spring-loaded test probe

GKS-005 206 396 A 5000

Item GKS-005-0002

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB

Learn more about
ICT/FCT Test probes

ingun.com

ICT/FCT TEST PROBES