

Radio Frequency Probes

HF86011B0032G830

Item number 1021014

General

Design	Coaxial Probe
Type/family	HF860
Pitch (mm/mil)	6,00 / 236
Temperature [C°]	-45°C...+100°C

Electrical specifications

Continuous current (A)	5.00
Impedance (ohm)	50.00
Frequency (GHz)	6.00
Continuous current 2 (A)	3.00

Inner contact specifications

Preload 2 (cN)	40.00
Spring force 2 (cN)	80.00

Mechanical specifications


Preload (cN)	450.00
Spring force (cN)	750.00
Nominal travel (mm)	3.00
Maximum travel (mm)	4.00
Tool size (mm)	3,5/4,0
DUT	PCB-GS

Dimensions

Total length (mm)	44.00
Projection height (mm)	12.50
Tip style diameter (mm)	8.00
Barrel diameter (mm)	4.50
Collar diameter (mm)	4.70
Press ring diameter (mm)	4.70
Inside/outside distance (mm)	1.00
Tip style diameter 2 (mm)	0.51

Family drawing

All measurements are in mm.



Materials & surfaces

Tip style	18
Tip style 2	11
Tip style material	Brass
Tip style plating	Gold
Plunger material	Cooper
Plunger plating	Gold
Barrel material	Brass
Barrel plating	Gold
Spring material	High-grade steel
Spring plating	Uncoated
Plunger material 2	Beryllium cooper
Plunger plating 2	Gold
Spring material 2	Spring steel
Spring plating 2	Gold