Radio-frequency probe


HFS-840 201 051 A 5302 S 4M


Item HFS-840-0617

GO TO PRODUCT

ingun®
Partner for Future Technology

- Long standard series
- Up to 4 GHz
- Cable interface MCX
- Screw-in version of asymmetrical probes, with additional crimp point to secure positioning
- Receptacles: KS-810 M5-R, KS-810 M5-F





PCB

Radio-frequency probe

HFS-840 201 051 A 5302 S 4M

Item HFS-840-0617

GO TO PRODUCT

ingun®
Partner for Future Technology

General data

Product group:	HFS radio-frequency test probes
Series:	HFS-840
Sub-series:	HFS-840 4M screw-in with adjustable positioning
Grid:	6.5 mm [255 mil]
DUT / contact:	PCB coax, open
Installation type:	Screw-in
Floating mount:	No
Non-rotating:	Yes
Continuous plunger:	Yes
Interface of compatible assembly:	MCX 50 Ohm
Compatible assembly interface gender :	M signal conductor male / pin
KS sub-series:	KS-810 M, screw-in version
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6a;6c

Outer conductor data

Outer conductor tip style:	02 flat
Outer conductor tip style diameter:	2.6 mm [.102 in]
Spring force of entire outer conductor at working stroke:	4 N [14.3 ozf]
Outer conductor working stroke:	4 mm [.157 in]
Outer conductor maximum stroke:	5 mm [.196 in]
Exchangeable outer conductor:	KO-810-0154
Outer conductor max. current load capacity:	10 A

Inner conductor data

Inner conductor tip style:	01 30° needle tip, self-cleaning
Inner conductor tip style diameter:	0.51 mm [.020 in]
Inner conductor tip style material:	2 steel
Inner conductor tip style surface:	A gold
Number of inner conductors:	1
Exchangeable inner conductor:	GKS-051-0001
Inner conductor working stroke:	2 mm [.078 in]
Spring force of each inner conductor at working stroke:	1.3 N [4.67 ozf]
Inner conductor maximum stroke:	3.7 mm [.145 in]
Inner conductor max. current load capacity:	2 A

Electrical data

Frequency range up to:	4 GHz
Impedance:	50 Ohm
Dielectric strength:	1.1 kV

Mechanical data

Total spring force at working stroke:	5.3 N [19.0 ozf]
Total length:	43 mm [1.69 in]
Barrel diameter:	4.5 mm [.177 in]
Installation height without receptacle:	11.5 mm [.452 in]
Torque in receptacle:	10 - 20 cNm [.885 - 1.77 lbf·in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Radio-frequency test probes

PCB

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com