Radio-frequency probe


HFS-836 288 120 A 4588A51F50L


Item HFS-836-0001

GO TO PRODUCT


ingun®
Partner for Future Technology


- For contacting test pads on PCBs (signal/ground structures)
- Up to 4 GHz
- Cable interface SMA
- Installation via flange mounting







1:1









PCB

Radio-frequency probe

HFS-836 288 120 A 4588A51F50L

Item HFS-836-0001

GO TO PRODUCT

ingun®
Partner for Future Technology

General data

Product group:	HFS radio-frequency test probes
Series:	HFS-836
Sub-series:	HFS-836
Grid:	13.2 mm [519 mil]
DUT / contact:	PCB pad GSG
Installation type:	Flange
Floating mount:	No
Non-rotating:	Yes
Continuous plunger:	No
Interface of compatible assembly:	SMA 50 Ohm
Compatible assembly interface gender :	M signal conductor male / pin
Recommended torque at interface:	45 cNm [3.98 lbf·in]
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6a;6c

Outer conductor data

Outer conductor tip style:	88 8-point,crown, self-cleaning
Outer conductor tip style diameter:	12.7 mm [.5 in]
Spring force of entire outer conductor at working stroke:	3 N [10.7 ozf]
Outer conductor working stroke:	4.3 mm [.169 in]
Outer conductor maximum stroke:	6.2 mm [.244 in]
Exchangeable outer conductor:	GKS-075-0135
Outer conductor max. current load capacity:	3 A

Inner conductor data

Inner conductor tip style:	88 8-point,crown, self-cleaning
Inner conductor tip style diameter:	1.2 mm [.047 in]
Inner conductor tip style material:	2 steel
Inner conductor tip style surface:	A gold
Number of inner conductors:	1
Exchangeable inner conductor:	GKS-075-0135
Inner conductor working stroke:	4.3 mm [.169 in]
Spring force of each inner conductor at working stroke:	1.5 N [5.39 ozf]
Inner conductor maximum stroke:	6.2 mm [.244 in]
Inner conductor max. current load capacity:	2 A

Electrical data

Frequency range up to:	4 GHz
Impedance:	50 Ohm

Mechanical data

Total spring force at working stroke:	4.5 N [16.1 ozf]
Total length:	46.5 mm [1.83 in]
Barrel diameter:	12.7 mm [.5 in]
Installation height without receptacle:	38.5 mm [1.51 in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Radio-frequency test probes

PCB

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com