Spring-loaded test probe


GKS-899 305 050 A 0702 M


Item GKS-899-0067

GO TO PRODUCT

ingun®
Partner for Future Technology

- Screw-in test probes for applications with possible vibrations or unwanted side and axial forces (migration of the test probe out of the receptacle is reliably prevented)
- The screw-in test probe is securely installed in the KS using a torque screwdriver and bit tool. The required screw-in torque is applied via a square post on the receptacle.





General data

Product group:	Screw-in test probe
Sub-product group:	Screw-in test probe
Series:	GKS-899 M screw-in
Grid:	2.54 mm [100 mil]
Contacting from:	Pad, Female connector
Magnetic:	Yes
Installation type:	Screw-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Screw-in torque:	2 - 3 cNm [.177 - .265 lbf·in]
Compatible receptacle(s):	KS-899 M
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	5 A
Typical resistance (Ri):	<20 mOhm

Mechanical data

Total length:	27.9 mm [1.09 in]
Barrel diameter:	1.37 mm [.053 in]
Maximum stroke:	4.4 mm [.173 in]
Spring pre-load:	0.3 N [1.07 ozf]
Collar height:	02
Spring force at working stroke:	0.7 N [2.51 ozf]
Recommended working stroke:	3.5 mm [.137 in]

Tip style data

Tip style:	05 bullet-nosed (full radius)
Tip diameter:	0.5 mm [.019 in]
Tip style surface:	A gold
Tip style material:	3 CuBe

SCREW-IN TEST PROBE


Spring-loaded test probe

GKS-899 305 050 A 0702 M

Item GKS-899-0067

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Screw-in test probe

SCREW-IN TEST PROBE

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com