# High-current probe


## HSS-118 317 200 A 2209


Item HSS-118-0259


GO TO PRODUCT

ingun®
Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights




### General data

| | |
|---|---|
| Product group: | High-current test probe |
| Sub-product group: | Standard HSS (press-in) |
| Series: | HSS-118 |
| Grid: | 2.54 mm [100 mil] |
| Contacting from: | Pad, Via, Female connector |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible receptacle(s): | KS-112 |
| Min. temperature: | - 100 °C [- 212 °F] |
| Max. temperature: | + 200 °C [+ 392 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 20 A |
| Typical resistance (Ri): | <10 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 39.3 mm [1.54 in] |
| Barrel diameter: | 1.66 mm [.065 in] |
| Maximum stroke: | 5.3 mm [.208 in] |
| Spring pre-load: | 0.61 N [2.19 ozf] |
| Collar height: | 09 |
| Spring force at working stroke: | 2.25 N [8.09 ozf] |
| Recommended working stroke: | 4 mm [.157 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 17 hexagonal pyramid with cutting edges, self-cleaning |
| Tip diameter: | 2 mm [.078 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |

HIGH-CURRENT TEST PROBE


# High-current probe

## HSS-118 317 200 A 2209

Item HSS-118-0259

GO TO PRODUCT

Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
**High-current test probe**

HIGH-CURRENT TEST PROBE

Prices and delivery times on request.
Technical changes reserved. 01/25_GB



ingun.com