Spring-loaded test probe

GKS-080 301 035 A 0805 E

Item GKS-080-0016

GO TO PRODUCT

ingun®
Partner for Future Technology





General data

Product group:	ICT / FCT (in-circuit test and function test
Sub-product group:	Fine-pitch
Series:	GKS-080 E installation with KS
Grid:	1 mm [40 mil]
Contacting from:	Pad
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-080
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	3 A
Typical resistance (Ri):	<20 mOhm

Mechanical data

Total length:	19.3 mm [.759 in]
Barrel diameter:	0.7 mm [.027 in]
Maximum stroke:	3.8 mm [.149 in]
Spring pre-load:	0.07 N [.251 ozf]
Collar height:	05
Spring force at working stroke:	0.8 N [2.87 ozf]
Recommended working stroke:	3 mm [.118 in]

Tip style data

Tip style:	01 30° needle tip, self-cleaning
Tip diameter:	0.35 mm [.013 in]
Tip style surface:	A gold
Tip style material:	3 CuBe

Spring-loaded test probe

GKS-080 301 035 A 0805 E

Item GKS-080-0016

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB