# Spring-loaded test probe


## GKS-113 302 080 A 1002 M


Item GKS-113-1204

GO TO PRODUCT

Partner for Future Technology

- Screw-in test probes for applications with possible vibrations or unwanted side and axial forces (migration of the test probe out of the receptacle is reliably prevented)
- The screw-in test probe is securely installed in the KS using a torque screwdriver and bit tool. The required screw-in torque is applied via a square post on the receptacle.
- Stainless steel versions for temperatures from -100 °C up to +200 °C available




### General data

| | |
|---|---|
| Product group: | Screw-in test probe |
| Sub-product group: | Screw-in test probe |
| Series: | GKS-113 M screw-in |
| Grid: | 4 mm [157 mil] |
| Contacting from: | Pin, posts, bead, flat contact |
| Magnetic: | Yes |
| Installation type: | Screw-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Screw-in torque: | 10 - 20 cNm [.885 - 1.77 lbf·in] |
| Compatible receptacle(s): | KS-113 M |
| Min. temperature: | - 40 °C [- 104 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 5 A |
| Typical resistance (Ri): | <30 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 28.3 mm [1.11 in] |
| Barrel diameter: | 2.65 mm [.104 in] |
| Maximum stroke: | 5.3 mm [.208 in] |
| Spring pre-load: | 0.33 N [1.18 ozf] |
| Collar height: | 02 |
| Spring force at working stroke: | 1 N [3.59 ozf] |
| Recommended working stroke: | 4 mm [.157 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 02 flat |
| Tip diameter: | 0.8 mm [.031 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |

SCREW-IN TEST PROBE


# Spring-loaded test probe

## GKS-113 302 080 A 1002 M

Item GKS-113-1204

GO TO PRODUCT

ingun®
Partner for Future Technology




ingun.address

Learn more about
**Screw-in test probe**

Prices and delivery times on request.
Technical changes reserved. 02/25_GB



ingun.com

SCREW-IN TEST PROBE