Dipole clamp, round contact

VKR-672 400 090 S 15804 M-VZ


Item VKR-672-0019

GO TO PRODUCT


ingun®
Partner for Future Technology


- VKR-672 sereis as insert for four-pole measurement
- High-current clamp for scratch-free contacting of round posts and threads
- During the contacting process, the contact lamellae are pressed securely against the post without scratching it.
- Due to the probe design, they are particularly suitable for applications with vibrations, dirt, and longer test cycles, as well as for round contacts with shock-proof protection.












Example of contact at working stroke



General data

Product group:	High-current test probe
Sub-product group:	Clamp contact, round, dipole
Series:	VKR-672 M screw-in
Grid:	7.5 mm [295 mil]
Contacting from:	Post
Magnetic:	Yes
Installation type:	Screw-in
Quick-exchange system:	Yes
Type of test probe connection:	Thread connection
Adjustable installation height:	No
Non-rotating:	No
Screw-in torque:	10 - 20 cNm [.885 - 1.77 lbf·in]
Compatible receptacle(s):	KS-622 M
Min. temperature:	- 100 °C [- 212 °F]
Max. temperature:	+ 200 °C [+ 392 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	40 A
Typical resistance (Ri):	<1 mOhm

Mechanical data

Total length:	78 mm [3.07 in]
Barrel diameter:	5 mm [.196 in]
Maximum stroke:	5.5 mm [.216 in]
Spring pre-load:	5.82 N [20.9 ozf]
Collar height:	04
Spring force at working stroke:	15.8 N [56.8 ozf]
Recommended working stroke:	4 mm [.157 in]

Tip style data

Tip style:	00 flat with bore
Tip diameter:	6.9 mm [.271 in]
Tip style surface:	S silver
Tip style material:	3 CuBe


Dipole clamp, round contact

VKR-672 400 090 S 15804 M-VZ

Item VKR-672-0019

GO TO PRODUCT

Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB