Coaxial cable, pre-wired


SE-EF178-50MCXMW080SMAMG

Item SE-EF178-0010

GO TO PRODUCT


ingun®
Partner for Future Technology

- Plug or cable assemblies for RF test probes (HFS)



1:1





General data

Product group:	Assemblies
Series:	SE-EF178
Sub-series:	SE-EF178 plug
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 105 °C [+ 221 °F]
RoHS-compliant:	RoHS-3

Cable data

Cable length:	80 cm [31.4 in]
Cable type:	ENVIROFLEX_178
Kink protection cable:	Shrink-on sleeve, black, 20 mm
Attenuation Fmax:	2.48 dB

Connector data

Interface 1:	MCX
Interface gender 1:	M signal conductor male / plug
Version 1:	Right angle
Interface 2:	SMA
Interface gender 2:	M signal conductor male / plug
Version 2:	Straight
Moment interface 2:	45 cNm [3.98 lbf·in]

Electrical data

Maximum frequency:	3 GHz
Impedance:	50 Ohm
Cable shielding:	Simple
Maximum performance:	35 W
Performance coefficient:	60 EF178
Dielectric strength:	0.75 kV
Attenuation coefficient a:	1,40670 EF178
Attenuation coefficient b:	0,22290 EF178

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

PLUG AND CABLE

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com