Spring-loaded test probe

GKS-075 291 064 A 1002 MLP

Item GKS-075-1634

GO TO PRODUCT

ingun®
Partner for Future Technology

General data

Series:	GKS-075 MLP long version, screw-in
Grid:	1.91 mm [75 mil]
Contacting from:	Pad, via
Compatible receptacle(s):	KS-075 M
RoHS-compliant:	RoHS-3;6a;6c

Electrical data


Current load capacity / rated current:	3 A

Mechanical data

Total length:	37.9 mm [1.49 in]
Barrel diameter:	1 mm [.039 in]
Maximum stroke:	6.35 mm [.25 in]
Spring pre-load:	0.4 N [1.43 ozf]
Collar height:	02
Spring force at working stroke:	1 N [3.59 ozf]
Recommended working stroke:	4.3 mm [.169 in]

Tip style data

Tip style:	91 dagger, self-cleaning
Tip diameter:	0.64 mm [.025 in]
Tip style surface:	A gold
Tip style material:	2 steel



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Screw-in test probe

SCREW-IN TEST PROBE

Prices and delivery times on request.
Technical changes reserved. 01/25_GB

ingun.com