# Test probe, INGUN S-Line

## S-050 306 115 A 1200 L

Item S-050-0006

GO TO PRODUCT


Partner for Future Technology

- Use of larger test probes for increased contacting accuracy and longer service life
- Minimal grid dimensions due to omission of receptacles (socketless)
- Large selection of tip styles and spring forces for optimal contact with the test point
- Compatible with existing socketless systems

NEW



1:1




### General data

| | |
|---|---|
| Product group: | ICT / FCT (in-circuit test and function test |
| Sub-product group: | INGUN S-Line |
| Series: | S-050 L long version |
| Grid: | 1.27 mm [50 mil] |
| Contacting from: | Pin, Post, Flat contact |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Type of test probe connection: | Contact terminal |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Min. temperature: | - 40 °C [- 104 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 4 A |
| Typical resistance (Ri): | <20 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 39.62 mm [1.55 in] |
| Barrel diameter: | 1.02 mm [.040 in] |
| Maximum stroke: | 10 mm [.393 in] |
| Spring pre-load: | 0.21 N [.755 ozf] |
| Collar height: | 00 |
| Spring force at working stroke: | 1.2 N [4.31 ozf] |
| Recommended working stroke: | 8 mm [.314 in] |
| Mounting hole in probe plate (KTP): | 1.07 - 1.09 mm [.042 - .042 in] |
| Mounting hole in S-Line spacer plate (SDP): | min. 1.14 mm [.044 in] |
| KT designation: | KT-S050 |

### Tip style data

| | |
|---|---|
| Tip style: | 06 serrated |
| Tip diameter: | 1.15 mm [.045 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |

ICT/FCT TEST PROBES


# Test probe, INGUN S-Line

## S-050 306 115 A 1200 L

Item S-050-0006

GO TO PRODUCT

Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB



Learn more about
**ICT/FCT Test probes**

ingun.com

ICT/FCT TEST PROBES