Radio-frequency probe


HFS-810 303 090 A 5340 GT13


Item HFS-810-0409


GO TO PRODUCT

ingun®
Partner for Future Technology


- Long standard series
- Up to 2 GHz
- Cable interface MCX
- Plug-in version
- Receptacles: KS-810, KS-810 R, KS-810 F









1:1







RADIO-FREQUENCY TEST PROBES

Radio-frequency probe

HFS-810 303 090 A 5340 GT13

Item HFS-810-0409

GO TO PRODUCT

Partner for Future Technology

General data

Product group:	HFS radio-frequency test probes
Series:	HFS-810
Sub-series:	HFS-810
Grid:	7 mm [275 mil]
DUT / contact:	GT13
Installation type:	Plug-in
DUT interface gender :	M signal conductor male / pin
Floating mount:	No
Non-rotating:	Yes
Continuous plunger:	Yes
Interface of compatible assembly:	MCX 50 Ohm
Compatible assembly interface gender :	M signal conductor male / pin
KS sub-series:	KS-810, press-in version
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Outer conductor data

Outer conductor tip style:	40 tip with traverse groove
Outer conductor tip style diameter:	6.5 mm [.255 in]
Spring force of entire outer conductor at working stroke:	4 N [14.3 ozf]
Outer conductor working stroke:	4 mm [.157 in]
Outer conductor maximum stroke:	5 mm [.196 in]
Exchangeable outer conductor:	KO-810140650A-GT13
Outer conductor max. current load capacity:	3 A

Inner conductor data

Inner conductor tip style:	03 inverse cone
Inner conductor tip style diameter:	0.9 mm [.035 in]
Inner conductor tip style material:	3 CuBe
Inner conductor tip style surface:	A gold
Number of inner conductors:	1
Exchangeable inner conductor:	GKS-051-0017
Inner conductor working stroke:	2 mm [.078 in]
Spring force of each inner conductor at working stroke:	1.3 N [4.67 ozf]
Inner conductor maximum stroke:	3.7 mm [.145 in]
Inner conductor max. current load capacity:	3 A

Electrical data

Frequency range up to:	2 GHz
Impedance:	50 Ohm
Dielectric strength:	1.1 kV

Mechanical data

Total spring force at working stroke:	5.3 N [19.0 ozf]
Total length:	45 mm [1.77 in]
Barrel diameter:	4.5 mm [.177 in]
Installation height without receptacle:	13.5 mm [.531 in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Radio-frequency test probes

Prices and delivery times on request.
Technical changes reserved. 01/25_GB

ingun.com

RADIO-FREQUENCY TEST PROBES