Receptacle

KS-069 30 G

Item KS-06930G

GO TO PRODUCT


Partner for Future Technology

INGUN SELECTION



1:1





General data

Product group:	Receptacles (KS)
Series:	KS-069
Sub-series:	KS-069 press-in version
Type of receptacle connection:	Solder
Press ring:	Yes
Surface area:	Gold
Collar diameter:	0.94 mm [.037 in]
Collar height:	2.54 mm [.1 in]
Knurl:	No
Vacuum-tight:	No
RoHS-compliant:	RoHS-3

Mounting hole

Mounting hole in CEM1:	0.86 - 0.92 mm [.033 - .036 in]
Mounting hole in FR4:	0.86 - 0.92 mm [.033 - .036 in]
Mounting hole with press ring in CEM1:	0.86 - 0.92 mm [.033 - .036 in]
Mounting hole with press ring in FR4:	0.86 - 0.92 mm [.033 - .036 in]

Mechanical data

Total length:	17.5 mm [.688 in]
Outer diameter:	0.86 mm [.033 in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB