

Basic Threaded Probes

F73216B064G150

Item number 1005107

General

Design	Basic Contact Probe
Type/family	F732
Pitch (mm/mil)	2,54 / 100
Temperature [C°]	-45°C...+100°C

Electrical specifications

Continuous current (A)	5.00
Typical contact resistance (mOhm)	25.00

Mechanical specifications


Preload (cN)	60.00
Spring force (cN)	150.00
Nominal travel (mm)	4.00
Maximum travel (mm)	5.00
Pointing accuracy +/- (mm)	0.08
Thread	M1,6
Tool size (mm)	1,7

Dimensions

Total length (mm)	35.70
Projection height (mm)	10.30
Tip style diameter (mm)	0.64
Barrel diameter (mm)	1.65
Collar diameter (mm)	2.30
Press ring diameter (mm)	2.30
B – spade width (mm)	1.00
C – spade length (mm)	5.00
D – plate diameter (mm)	1.00
B – plate diameter (mm)	1.00
C – pin length (mm)	5.00

Family drawing

All measurements are in mm.



Materials & surfaces

Tip style	16
Tip style material	Beryllium cooper
Tip style plating	Gold
Plunger material	Cooper
Plunger plating	Gold
Barrel material	Brass
Barrel plating	Gold
Spring material	Spring steel
Spring plating	Silver

Accessories

Tool for receptacle	FEWZ-772E0