Spring-loaded test probe

GKS-313 302 100 A 1502 M


Item GKS-313-0010


GO TO PRODUCT

ingun®
Partner for Future Technology


list

Text-block





1:1



SCREW-IN TEST PROBE

Spring-loaded test probe

GKS-313 302 100 A 1502 M

Item GKS-313-0010

GO TO PRODUCT

Partner for Future Technology

General data

Product group:	Screw-in test probe
Sub-product group:	Screw-in test probe
Series:	GKS-313 M screw-in
Grid:	4.5 mm [177 mil]
Contacting from:	Pin, posts, bead, flat contact
Magnetic:	Yes
Installation type:	Screw-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Screw-in torque:	10 - 20 cNm [.885 - 1.77 lbf·in]
Compatible receptacle(s):	KS-313 M
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data


Current load capacity / rated current:	5 A
Typical resistance (Ri):	<30 mOhm

Mechanical data

Total length:	62.8 mm [2.47 in]
Barrel diameter:	2.65 mm [.104 in]
Maximum stroke:	14.3 mm [.562 in]
Spring pre-load:	0.21 N [.755 ozf]
Collar height:	02
Spring force at working stroke:	1.5 N [5.39 ozf]
Recommended working stroke:	12 mm [.472 in]

Tip style data

Tip style:	02 flat
Tip diameter:	1 mm [.039 in]
Tip style surface:	A gold
Tip style material:	3 CuBe



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Screw-in test probe

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com

SCREW-IN TEST PROBE