Spring-loaded test probe


GKS-365 113 400 A 8001 S


Item GKS-365-0076


GO TO PRODUCT

ingun®
Partner for Future Technology

- Extremely robust test probes for applications with unwanted side and axial forces
- For use in applications with limited space







General data

Product group:	Assorted test probes
Sub-product group:	Short stroke GKS / charge and transfer GKS
Series:	GKS-365 S special tip style
Grid:	6.5 mm [255 mil]
Contacting from:	Pad, Female connector
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-365
Min. temperature:	- 100 °C [- 212 °F]
Max. temperature:	+ 200 °C [+ 392 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	8 A
Typical resistance (Ri):	<30 mOhm

Mechanical data

Total length:	15 mm [.590 in]
Barrel diameter:	4.97 mm [.195 in]
Maximum stroke:	4 mm [.157 in]
Spring pre-load:	3.08 N [11.0 ozf]
Collar height:	01
Spring force at working stroke:	8 N [28.7 ozf]
Recommended working stroke:	3.2 mm [.125 in]

Tip style data

Tip style:	13 30° needle tip, rounded
Tip diameter:	4 mm [.157 in]
Tip style surface:	A gold
Tip style material:	1 brass


Spring-loaded test probe

GKS-365 113 400 A 8001 S

Item GKS-365-0076

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com