Test Probe


GKS-422 209 080 N 5008


Item GKS-422-0052

GO TO PRODUCT

ingun®
Partner for Future Technology

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Version with central beading ensure low wobble for contacting small test points
- Stainless steel versions for temperatures from -100 °C up to +200 °C available





General data

Product group:	ICT / FCT (in-circuit test and function test
Sub-product group:	Metric standard
Series:	GKS-422
Grid:	2.54 mm [100 mil]
Contacting from:	Pad, pin
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-112
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	5 A
Typical resistance (Ri):	<20 mOhm

Mechanical data

Total length:	38.4 mm [1.51 in]
Barrel diameter:	1.66 mm [.065 in]
Maximum stroke:	8 mm [.314 in]
Spring pre-load:	0.9 N [3.23 ozf]
Collar height:	08
Spring force at working stroke:	5 N [17.9 ozf]
Recommended working stroke:	6.4 mm [.251 in]

Tip style data

Tip style:	09 flexi-needle, self-cleaning
Tip diameter:	0.8 mm [.031 in]
Tip style surface:	N nickel
Tip style material:	2 steel


Test Probe

GKS-422 209 080 N 5008

Item GKS-422-0052

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 01/25_GB