Spring-loaded test probe


GKS-001 306 150 A 1502 M

Item GKS-001-0059

GO TO PRODUCT

ingun®
Partner for Future Technology





General data

Product group:	Screw-in test probe
Sub-product group:	Screw-in test probe
Series:	GKS-001 M
Grid:	1.91 mm [75 mil]
Contacting from:	Pin, Post, Flat contact
Magnetic:	Yes
Installation type:	Screw-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Screw-in torque:	0.5 - 1 cNm [.044 - .088 lbf·in]
Compatible receptacle(s):	KS-001 M
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	4 A
Typical resistance (Ri):	<20 mOhm

Mechanical data

Total length:	19 mm [.748 in]
Barrel diameter:	1 mm [.039 in]
Maximum stroke:	3 mm [.118 in]
Spring pre-load:	0.47 N [1.69 ozf]
Collar height:	02
Spring force at working stroke:	1.5 N [5.39 ozf]
Recommended working stroke:	2.4 mm [.094 in]

Tip style data

Tip style:	06 serrated
Tip diameter:	1.5 mm [.059 in]
Tip style surface:	A gold
Tip style material:	3 CuBe

SCREW-IN TEST PROBE


Spring-loaded test probe

GKS-001 306 150 A 1502 M

Item GKS-001-0059

GO TO PRODUCT

ingun®
Partner for Future Technology



INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

Learn more about
Screw-in test probe

ingun.com

SCREW-IN TEST PROBE