HSAL2 6-Pin

SE-HSAL2-06-M-G-000


Item 114729

GO TO PRODUCT

Partner for Future Technology

- Cable adapter for test plug 114729 (PS-HSAL2-M-006-G5-B-01)
- For soldering cables - stranded wires AWG 25 and higher - to the test system.
- Shielded housing
- Adjustable cable strain relief


NEW



1:1

Function and installation:

When soldering the contact element with an individual cable, 6-pole, AWG 25, or higher, solder in the slot of the pins to ensure the solder joint does not protrude beyond the outer diameter of the contact element. Press the contact elements in fully using the SW-ZW-GKS-075 insertion tool. Observe the specific pin configuration (1-12). Then screw the housing onto the test plug using 2x M1.6 screws and tighten the cable strain relief if required.



General data

Product group:	Plug (SE)
Series:	SE-HSAL
Sub-series:	SE-HSAL connector
Min. temperature:	+ 0 °C [+ 32 °F]
Max. temperature:	+ 50 °C [+ 122 °F]
RoHS-compliant:	RoHS-3;6c

Connector data

Interface 1:	HSAutolink2
Interface gender 1:	F signal conductor female / socket
Version 1:	Straight

PLUG AND CABLE


HSAL2 6-Pin


SE-HSAL2-06-M-G-000


Item 114729


GO TO PRODUCT

ingun®
Partner for Future Technology









INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

Prices and delivery times on request.
Technical changes reserved. 01/25_GB

ingun.com

PLUG AND CABLE