# Pneumatic test probe


## PKS-300 201 200 R 1102 B


Item PKS-300-0002

GO TO PRODUCT


ingun®
Partner for Future Technology


- Universal pneumatic probes for a wide range of applications, e.g., for contacting test pads, activation of switches, contacting of difficult-to-access test points, or creation of interfaces.
- When using PKS probes, a separate actuating mechanism may not be necessary
- PKS are retracted in the home position. When pressure is applied, the plunger extends
- The electrical connection is ensured by installation using a receptacle





# Pneumatic test probe

## PKS-300 201 200 R 1102 B

Item PKS-300-0002

GO TO PRODUCT

Partner for Future Technology

### General data

| | |
|---|---|
| Product group: | Pneumatic test probe |
| Sub-product group: | PKS (pressed in) |
| Series: | PKS-300 B long version |
| Grid: | 3.5 mm [137 mil] |
| Contacting from: | Pad |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | No |
| Type of test probe connection: | Clip |
| PKS operating pressure: | 6 bar [87.0 psi] |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible connector(s): | KL-300 |
| Compatible receptacle(s): | KS-300 |
| Min. temperature: | + 0 °C [+ 32 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6a;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 2 A |
| Typical resistance (Ri): | <30 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 42.7 mm [1.68 in] |
| Barrel diameter: | 3 mm [.118 in] |
| Maximum stroke: | 10 mm [.393 in] |
| Spring pre-load: | 0.5 N [1.79 ozf] |
| Collar height: | 02 |
| Spring force at working stroke: | 1.1 N [3.95 ozf] |
| Recommended working stroke: | 6 mm [.236 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 01 30° needle tip, self-cleaning |
| Tip diameter: | 2 mm [.078 in] |
| Tip style surface: | R rhodium |
| Tip style material: | 2 steel |

**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
**Test probes**

Prices and delivery times on request.
Technical changes reserved. 02/25_GB



ingun.com