Test Probe

GKS-112 303 180 A 0606


Item GKS-112-1159


GO T

ingun

Partner for Future Techno

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available





General data

Product group:	ICT / FCT (in-circuit test and function test
Sub-product group:	Metric standard
Series:	GKS-112
Grid:	2.54 mm [100 mil]
Contacting from:	Pin, posts
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-112
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Electrical data

Current load capacity / rated current:	
Typical resistance (Ri):	<20 mO

Mechanical data

Total length:	36.3 mm [1.42
Barrel diameter:	1.66 mm [.065
Maximum stroke:	5.3 mm [.208
Spring pre-load:	0.2 N [.719 o
Collar height:	
Spring force at working stroke:	0.6 N [2.15 o
Recommended working stroke:	4 mm [.157

Tip style data

Tip style:	03 inverse co
Tip diameter:	1.8 mm [.070
Tip style surface:	A g
Tip style material:	3 Cu

ingun.com