# Spring-loaded test probe


## GKS-746 320 150 100 A 3002 M


Item GKS-746-0015

GO TO PRODUCT

ingun®
Partner for Future Technology




### General data

| | |
|---|---|
| Product group: | Screw-in test probe |
| Sub-product group: | Non-rotating test probes |
| Series: | GKS-746 M screw-in |
| Grid: | 2.54 mm [100 mil] |
| Contacting from: | Female connector |
| Magnetic: | Yes |
| Installation type: | Screw-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | Yes |
| Continuous plunger: | ø0,8 x 0,46 x 4,4 |
| Screw-in torque: | 3 - 5 cNm [.265 - .442 lbf·in] |
| Compatible receptacle(s): | KS-746 M |
| Min. temperature: | - 40 °C [- 104 °F] |
| Max. temperature: | + 80 °C [+ 176 °F] |
| RoHS-compliant: | RoHS-3;6c |

### Electrical data

| | |
|---|---|
| Current load capacity / rated current: | 8 A |
| Typical resistance (Ri): | <30 mOhm |

### Mechanical data

| | |
|---|---|
| Total length: | 40.2 mm [1.58 in] |
| Barrel diameter: | 1.65 mm [.064 in] |
| Maximum stroke: | 4.4 mm [.173 in] |
| Spring pre-load: | 1.21 N [4.35 ozf] |
| Collar height: | 02 |
| Spring force at working stroke: | 3 N [10.7 ozf] |
| Recommended working stroke: | 4 mm [.157 in] |

### Tip style data

| | |
|---|---|
| Tip style: | 20 spade, flat, bevelled, self-cleaning |
| Tip diameter: | 1.5 mm [.059 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |
| Spade width: | 1 mm [.039 in] |
| Spade length: | 3.8 mm [.149 in] |

SCREW-IN TEST PROBE


# Spring-loaded test probe

## GKS-746 320 150 100 A 3002 M

Item GKS-746-0015

GO TO PRODUCT

ingun®
Partner for Future Technology




**INGUN Prüfmittelbau GmbH**
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
**Screw-in test probe**

Prices and delivery times on request.
Technical changes reserved. 02/25_GB



ingun.com

SCREW-IN TEST PROBE